





PERFORMANCE SPECIFICATIONS

.35 dB LOSS PER JUNCTION @ 850 nm TYPICAL,
.5 dB MAX (@ ROOM TEMPERATURE)

OPERATING TEMPERATURE: -40°C TO 150°C

200°C BAKEOUT FOR 1 HOUR

LEAK RATE <1 X 10E-9 ATM-CC/SEC (He)




***SEE SHEET 2 FOR INSTALLATION AND MOUNTING DETAILS**


PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.					THIRD ANGLE PROJECTION 			TITLE: MM FEEDTHROUGH, FC-ST		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	12/10/2018	PART NO. FA38314 REV. A		SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA38314SL REV. A2	
A2	JF	12/18/2018	FOFDN001-30		ENG APPR.	JF	12/10/2018				

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.

INSTALLED VIEW



MOUNTING DIMENSIONS



WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA38314SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

MM FEEDTHROUGH, FC-ST

PART NO. FA38314 REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN	DRAWN	JF	12/10/2018
A2	JF	12/18/2018	OFD001-30_MOUNTING	INCHES [mm]	ENG APPR.	JF	12/10/2018

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.