





PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-200°C TO 200°C

CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J
ALUMEL (-)	B,D,F,H,K

REFER TO INSTRUCTION SHEET "NS41399" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE TYPE K 5 PAIR VACUUM SIDE PLUG				 SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/11/2020	PART NO. FA41399 REV. A	WWW.SOLIDSEALING.COM		
A3	JF	07/08/2021	MSME0005-11		ENG APPR.	JF	9/11/2020		SALES DWG NO. FA41399SL REV. A3		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.