



THIS INSTRUCTION SHEET APPLIES TO PLUG FA41289 USED WITH CONTACTS KT41236 OR KT41236-02.

ASSEMBLY INSTRUCTIONS:

- 1- STRIP WIRE INSULATION TO EXPOSE .060-.090" [1.53-2.28 mm] OF WIRE CORE. INSERT STRIPPED WIRES THROUGH SKID WASHER AND REAR INSERT. CRIMP WIRE TO CONTACTS. CRIMP USING FP41735 CRIMP TOOL (CRIMP SETTING 5) WITH FP41731 LOCATOR.
- 2- AFTER CRIMPING SEAT CONTACTS INTO REAR INSERT.
- 3- INSERT REAR INSERT INTO FRONT INSERT MAKING SURE THE CONTACTS HAVE FULLY SEATED INTO THE FRONT INSERT. THIS IS VISUALLY CONFIRMED WHEN THE SHOULDERS ON BOTH INSERTS ARE NEARLY TOUCHING.
- 4- INSTALL INSERT ASSEMBLY INTO COUPLING NUT, THEN INSTALL SKID WASHER AND RETAINING RING INSIDE COUPLING NUT.
- 5- CONTACTS ACCEPT A 28-32 AWG WIRE SIZE FOR CRIMP.
- 6- MAXIMUM WIRE INSULATION OD: .030" [0.76 mm]



INSERTS SHOULD BE NEARLY TOUCHING WHEN CONTACTS ARE FULLY SEATED



PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE: INSTRUCTION SHEET MICRO C PLUG ASSEMBLY					
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	3/29/2021	NUMBER: NS41289	REV:	B	SHEET 1 OF 1
B	JF	04/21/2021	MSPLR004-07WS		ENG APPR.	JF	3/29/2021				